

# POUR POINT DEPRESSANT

## TECHNICAL DATA SHEET



### Components

Ingredient	CAS No.	Content ( Wt%)
Ethylene vinyl acetate copolymer	24937-78-8	15 – 20
Poly(vinyl acetate-2-ethylhexyl acrylate)	25067-02-1	15 – 20
Isooctonal	70955-04-3	60 – 70
Proprietary solvent	Proprietary	0.5 – 2.0
Proprietary co-solvent	Proprietary	0.5 – 2.0

### Typical Physical Properties

Appearance	Highly flowable white slurry
Hazardous Rating	Non-regulated, non-flammable
Specific Gravity	0.95 ± 0.05
Flash Point	> 65°C
Freeze Point	< -40°C

### Product Application Specification

**Intended Application:** Pour point reduction for waxy, paraffin-rich crude oil

**PPD Depression:** 10 - 30°C @ dosage 50-200ppm

**Viscosity Reduction:** 40 - 90% @ dosage 50-200ppm

**Shelf Life:** 5 years



**THE MARK CORPORATION**  
THE MARK OF EXCELLENCE

Phone: 412-551-9893 • [info@themarkcorp.com](mailto:info@themarkcorp.com)  
[themarkcorp.com](http://themarkcorp.com)

**Pour Point Depressant:** The information in this bulletin is believed to be accurate, but all recommendations are made without warranty, since the conditions of use are beyond the manufacturer's control. The listed properties are illustrative only, and not product specifications. The manufacturer disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.